



Rough Terrain Scissor Lift

Model : DS-1622RT

Address : PAP-A-5/4/5, Chakan Industrial Area, Phase-4,
Nigoje Village, Tal - Khed, Pune - 410501

Contact: +91 7507364790/9011067039

Email: marketing2@daedalusind.com /
a.mayur@daedalusind.com

Specifications

Models		DS-1622 RT	
Measurements		Feet	Metric
Maximum Working Height*		A	52 ft / 16 m
Maximum Platform Height		B	45 ft / 14 m
Lowered Platform Height		C	6.5 ft / 2.0 m
Platform Length -	Without Extension	D	10.4 ft / 2.4 m
	With Extension	E	10.1 ft / 3.1 m
Extension Deck		F	2.9 ft / 0.9 m
Platform Width		G	7.2 ft / 2.2 m
Guardrail Height		H	3.2 ft / 1.0 m
Vehicle Dimensions	Height	I	9.8 ft / 3.0 m
	Length	J	10.1 ft / 3.1 m
	Width	K	7.3 ft / 2.25 m
Ground Clearance			0.65 ft / 200 mm

Productivity

Maximum Occupancy**	2/3 People
Lift Capacity	350/500 Kgs
Extension Deck Capacity	125 Kgs
Drive Speed	4 Kmph
Turning Radius - Outside	3.4 m
Raise / Lower Height	70 / 75
Control	Proportional Control
Drive	4WD(Hydraulic Drive)
Brakes	Hydraulic Release Brake
Tyres (Solid Non-Marking)	584mm X 254mm

Power

Power Source	24V / 48V DC (Eight 6V 225Ah)
Hydraulic Capacity	60L (15.8 gal)
Weight***	4500 Kgs

* The metric equivalent of working height adds 2 m to platform height.

** Max Occupancy should not in any circumstances be more than 2

*** Weight will vary depending on options and/or country standards.

Note : Images are for reference only. They are not to be considered for actual visual appearance.